

Technical Specification For Two Wheeler Motercycle (150-200 cc) Date: 2082/07/26

S.N.	CRITERIA	REQUIRED SPECIFICATION	REMARKS
1.	General	Two- Wheeler Motercycle	
		Manufactured In Current Year,	
		Suitable For Daily Road Use,	
		Operable Between 2 Deg. Celcius to	
		40 Deg. Celcius.	
2.	Engine General	Petrol Engine Developing Minimum	
		12-14 Nm Torque And Minimum 13-	
	and the second second second	15 PS Power.	
3.	Engine Capicity	4 Store Engine With 150-200 cc.	A CONTRACTOR OF THE PARTY OF TH
4.	Fuel System	As per Manufacturer Standard	. 91
		(Carburetor Or Fuel Injection)	
5.	Starting System	Self And Kick Start	A STATE OF THE PARTY OF THE PAR
6.	Clutch	Wet Type Multi-Plate	
7.	Transmission	5-Speed Or More	
8.	Suspension	Front Telescopec/Rear Monoshock	
		Or Dual Shock (as per	
	The state of the s	Manufacturer)	
9.	Break System	Front Disc Not less than 240 mm Dia	
10.	Wheel& Tyres	As Per Manufacture Standard For	
	The second secon	Road Use	
11.	Head Light	Led Or Halogen(as per	
		Manufacturer)	
12.	Overall Length	Minimum 2000 mm	
13.	Overall Width	Minimum 780-800 mm	
14.	Overall Height	Minimum 1050-1100 mm	· · · · · · · · · · · · · · · · · · ·
15.	Wheelbase	Minimum 1320 mm	
16.	Kerb Weight	Minimum 118-125 KG	
17.	Ground Clearance	Minimum 160-170 mm	and the second second
18.	Tools	General Maintenance tool Set shall	
	10010	be Supplied	the same and the same and the same and
19.	Colour	To be Chosen After Bid Acceptance	And the second s
20.	Emission Standard	As per Nepal Mass Emission	
	Emission Standard	Standard	
21.	Warranty	Minimum 1 Year Warranty After	
		Acceptance	and the second second
22.	Delivery Site	Rural Municipality Office, Kavre	
		Devitar	

